CIRLOCK

LOCKOUT / TAGOUT EQUIPMENT

Plug and Hose Lockout Device PLD-1 Instructions

APPLICATION:

Electrical Plug

Place the Electrical Plug to be locked, inside the PLD-1 bag. Close the bag around the plugs cable, by tightening the steel cable with the lock hasp. See pictures.

Close lock hasp and place a padlock through holes provided. Lock and attach Danger Tag. Ensure plug can not be removed from lockout bag.

Air Hose:

Place end of hose with coupling inside the PLD-1 bag. If coupling is small, Velcro tape supplied with bag can be wrapped around end to prevent it being pulled out of bag. Close and lock bag as per plug above. Ensure hose can not be removed from bag.







If the Plug or Hose can not be adequately secured in a locked position – the PLD-1 BAG SHALL NOT BE USED.

DISCLAIMER: Appropriate use of this product is the sole responsibility of the user in relation to health and safety regulations. Before using, user shall determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. Erik Larsen Pty Ltd t/as CIRLOCK is not responsible for any loss or damage arising from the use of this product, which is beyond Erik Larsen P/L control, and liability is restricted to the replacement of material proven faulty

Made by or for:

CIRLOCK

Ph: +61-(0)7-54452910 www.cirlock.com.au